

Blue Line Thimble

The Blue Line Thimble is compatible with high-performance, high-modulus synthetic fiber rope products such as AmSteel®-Blue, Force-8, and DPX™-75.



Description

The tubular gusseted design creates a high-strength thimble that protects the rope and maintains the proper bending radius when connected to mating hardware.

Specifications

Rope Diameter	Rope Circumference	Thimble Weight (lbs)	A Inches	B Inches	C Inches	D Inches	E Inches	F Inches
3/16" – 3/8"	9/16" – 1-1/8"	0.80	0.50"	3.3"	0.90"	0.20"	0.30"	0.90"
7/16" – 1/2"	1-1/4" – 1-1/2"	1.1	0.60"	3.7"	1.1"	0.20"	0.40"	1.2"
9/16" – 5/8"	1-3/4" – 2"	1.4	0.80"	4.4"	1.3"	0.20"	0.50"	1.8"
3/4" – 7/8"	2-1/4" – 2-3/4"	2.0	0.90"	4.9"	1.4"	0.20"	0.60"	1.9"
1" – 1-1/8"	3" – 3-1/2"	5.8	1.4"	7.5"	2.4"	0.30"	0.90"	2.9"
1-1/4" – 1-1/2"	3-3/4" – 4-1/2"	7.5	1.8"	9.0"	2.8"	0.30"	1.1"	3.7"
1-5/8" – 1-11/16"	5" – 5-1/4"	10.3	2.0"	10.0"	3.0"	0.30"	1.2"	3.8"
1-3/4" – 2"	5-1/2" – 6"	10.8	2.2"	10.6"	3.2"	0.30"	1.4"	3.9"

* For use with Ultra Blue-8 add 1/4" (6 mm) to the rope diameter to determine the appropriate thimble size.